

Product Data Sheet April 2021



Anti-Slip Domestic

Safety Treatment for Ceramic Tile, Quarry Tile, Terrazzo and unpainted concrete

Description	 Anti Slip Domestic is a fluoride based liquid safety treatment designed to control slipping on tiled and concrete floors - particularly when water is present.
Why Domestic	 Anti Slip "commercial formulation" has been used industrially for almost 10 years, and whilst household applications are obvious, the cost factor has been high. To overcome this factor the D.I.Y. domestic product has been developed to provide an economical solution.
How does it work	 Anti Slip Domestic creates a minute change in the surface texture of the floor with little or no change in appearance but providing an improvement in slip-resistance of up to 70%
How long does it last	• The floor surface will have to be worn down to affect the Anti Slip Treatment. It is not a coating which will peel off.
Instructions for Use	
Surface Preparation	 Make sure substrate is clean prior to treatment, mop floor with water to pre- wet surface prior to treatment
Application	 Anti Slip is poured undiluted into a bucket or pail and applied by mop, broom, brush, or squeegee directly onto the floor in three equal applications. Allow a few minutes between applications. <u>Do not allow the surface to dry.</u> After the final application thoroughly rinse the surface with water. Mop or squeegee dry if required. The cleaning effect will be obvious. The floor can be walked on immediately.
Cleaning	Clean all tools with warm soapy water
How safe is Anti-Slip	 Anti Slip is environmentally friendly. Those with sensitive skin should wear gloves, however no other safety precautions are required.

Viroseal Pty Ltd, 2/23 Gardens Drive, Willawong Qld 4110 P: 0732761033 F: 0732761022 Mobile: 0417784558



Where can I use Anti-Slip	 Anti Slip can be used in a range of locations around the house where there is concern for slip/fall accidents. Typica applications include pool surrounds, patios, bathrooms laundries, steps, kitchens, and entry foyers. The product may be used internally or externally and is not affected by ultraviolet rays.
Which Floors can be treated with Anti-slip	 Anti Slip is designed for use on ceramic tiles, including glazed and mosaic tiles, quarry tiles, terrazzo, and unpainted or unsealed concrete. All surfaces to be treated must be tested on a smal inconspicuous area to check for reaction with product or unwanted change in appearance Do not use on Porcelain Tiles.
Important Notification	
tin re of in ap or pr no su su w pa re	Il orders are accepted subject of our terms and conditions at me of purchase. Customers should always refer to the most ecent issue of the Technical Data Sheet for Anti-Slip, copies which will be provided on request. The information, and, particular, the recommendations relating to the oplication and use of Anti-Slip, are given in good faith based in Viroseal's current knowledge and experience of the roduct when properly stored, handled and applied under ormal conditions. In practice, the differences in materials, ubstrates and actual site conditions are such that no arranty in respect of merchantability or of fitness for a articular purpose nor any liability arising out of any legal elationship whatsoever, can be inferred either from this formation, or from any written recommendations, or from